

VENUS 44(IP65)

features

- . Pure diode, long life-span. High reliability
- . TEC dual temperature control, Wider environment operating temperature
- . RGB divergence at the same angle, color modulation at the same level, truly realize wide color .temperature modulation.
- . Has the practical independent appearance design, is the present 20 watt level smallest volume laser lamp, is convenient to carry the transportation.
- . Optional to build in Pangolin FB4, controlling via Ethernet, ArtNet, DMX, ILDA or SD card etc.

Specification:

Total laser power	: ≥ 44,000mW	Scan angle	: 45 degree
R G B	: 12, 000mW 16,000mW 16,000mW	Signal connector	: Ethernet,ArtNet,FB4-DMX
Wavelength	: R-637nm G-525nm B-445nm	Ingress Protection	: IP65
Beam divergence	: <1.0mrad(full angle)	Temperature control	: TEC
Beam diameter	: <8mm	Operatingtemperature:	: -10°C-40°C
Modulation	: >100KHz	Size	: L456xW310×H251mm
Modulation way	: linear analog modulation	Weight	: 36kg
Scanner type	: PT-A28	Operating voltage	: 100-240V50/60Hz
Scanning	: 25Kpps@8°	Power consumption	: 1200W

Product Views



front



back



right



left

Dimension

