

## VENUS 60(IP65)

### features

- . Pure diode, long life-span. High reliability.
- . Low beam divergence <1.0mrad(full angle),strong penetrating power.
- . RGB divergence at the same angle, color modulation at the same level, truly realize wide color .temperature modulation.
- . High quality scanning system, wide-angle scanning.
- . Professional rainproof design system (IP 65), with high-end waterproof connectors and \ efficient cooling, Heatsink area covers 40% of the laser case area, Venus RGB60,000 performs greatly even under any extreme weather.
- . Ideal for long distance beam shows & basic graphics projections, seaside installations, landmark special lighting, and fountain special effect etc.
- . Build in Pangolin FB4 control interface with network switch for professional control and wiring.

### Specification:

Total laser power	: ≥ 60,000mW	Scan angle	: 40 degree
R   G   B	: 15,000mW   20000mW   25000mW	Signal connector	: Ethernet,ArtNet,FB4-DMX
Wavelength	: R-637nm   G-525nm   B-445nm	IP	: IP65
Beam divergence	: <1.1mrad(full angle)	Temperature control	: TEC
Modulation	: >100KHz	Operating temperature	: -10°C-40°C
Modulation way	: linear analog modulation	Size	: L580xW375xH279mm
Scanner type	: PT-A25S	Weight	: 50kg
Scanning	: 25Kpps@8°	Operating voltage	: 100-240V50/60Hz
		Power consumption	: 2200W



Product Views



front



back



right



left



# Dimension

