

VENUS 11(IP65)

features

- . Pure diode, long life-span. High reliability
- . Low beam divergence <1.0mrad(full angle),strong penetrating power.
- . TEC dual temperature control, Wider environment operating temperature
- . RGB divergence at the same angle, color modulation at the same level, truly realize wide color .temperature modulation.
- . High quality scanning system, wide-angle scanning.
- . Full diodes, longer lifetime and higher reliability, pure white color balance. Its robust and sturdy design makes it perfect for medium sized venues and events.
- . Optional to build in Pangolin FB4, controlling via Ethernet, ArtNet or SD card etc.

Specification:

Total laser power	: ≥ 11,000mW	Signal connector	: Ethernet,ArtNet,FB4-DMX
R G B	: 3,000mW 4,000mW 4,000mW	Ingress rating	: IP65
Wavelength	: R-637nm G-525nm B-445nm	Temperature control	: TEC
Beam divergence	: <1.0mrad(full angle)	Operatingtemperature	: -10°C-40°C
Modulation	: >100KHz	Size	: L320xW238xH191mm
Modulation way	: linear analog modulation	Weight	: 15kg
Scanner type	: PT-A40H	Operating voltage	: 100-240V50/60Hz
Scanning	: 30Kpps@8°	Power consumption	: 350W
Max scan angle	: 45 degree		

Product Views



front



back



right



left

Dimension

