

## VENUS 22(IP65)

### features

- . Pure diode, long life-span. High reliability
- . TEC dual temperature control, Wider environment operating temperature
- . RGB divergence at the same angle, color modulation at the same level, truly realize wide color .temperature modulation.
- . Has the practical independent appearance design, is the present 20 watt level smallest volume laser lamp, is convenient to carry the transportation.
- . Optional to build in Pangolin FB4, controlling via Ethernet, ArtNet, DMX, ILDA or SD card etc.

### Specification:

Total laser power	: ≥ 22,000mW	Max scan angle	: 45degree
R   G   B	: 6,000mW   8,000mW   8,000mW	Signal connector	: Ethernet,ArtNet,FB4-DMX,
Wavelength	: R-637nm   G-525nm   B-445nm	IP	: IP65
Beam divergence	: <1.0mrad(full angle)	Temperature control	: TEC
Beam diameter	: <6mm	Operatingtemperature:	: -10°C-40°C
Modulation	: >100KHz	Size	: L391xW263xH231mm
Modulation way	: linear analog modulation	Weight	: 26kg
Scanner type	: PT-A30S	Operating voltage	: 100-240V50/60Hz
Scanning	: 30Kpps@8°	Power consumption	: 1000W

Product Views



front



back



right



left

Dimension

