

UNICORN 10

features

- . Pure diode, long life-span. High reliability
 - . Low beam divergence <1.2mrad(full angle),strong penetrating power.
 - . TEC dual temperature control, Wider environment operating temperature
 - . RGB divergence at the same angle, color modulation at the same level, truly realize wide color .temperature modulation.
 - . High quality scanning system, wide-angle scanning
 - . Optional to build in Pangolin FB4, controlling via Ethernet, ILDA, or SD card
- etc.

Specification:

Total laser power	: ≥ 10,000mW	Max scan angle	: 45 degree
R G B	: 3200mW 3200mW 4000mW	Signal connector	: Ethernet,ArtNet,DMX,ILDA
Wavelength	: R-638nm G-525nm B-450nm	protection rate	: indoor
Beam divergence	: <1.2mrad(full angle)	Temperature control	: TEC
Beam diameter	: <6mm	Operatingtemperature	: -10°C-40°C
Modulation	: >100KHz	Size	: L276xW219xH181mm
Modulation way	: linear analog modulation	Weight	: 8.5 kg
Scanner type	: PT-A40H	Operating voltage	: 100-240V50/60Hz
Scanning	: 30Kpps@8°	Power consumption	: 150W

Product Views



front



back



right



left

Dimension

