

UNICORN 30(IP65)

features

- . Pure diode, long life-span. High reliability
- . Low beam divergence <1.2mrad(full angle),strong penetrating power.
- . TEC dual temperature control, Wider environment operating temperature
- . RGB divergence at the same angle, color modulation at the same level, truly realize wide color .temperature modulation.
- . High quality scanning system, wide-angle scanning.
- . Full diodes, longer lifetime and higher reliability, pure white color balance. Its robust and sturdy design makes it perfect for medium sized venues and events.
- . Optional to build in Pangolin FB4, controlling via Ethernet, ArtNet or SD card etc.

Specification:

Total laser power	: ≥ 30,000mW	Max scan angle	: 45 degree
R G B	: 8,500mW 10,000mW 12, 000mW	Signal connector	: Ethernet,ArtNet,FB4-DMX
Wavelength	: R-638nm G-525nm B-450nm	protection rate	: IP65
Beam divergence	: <1.2mrad (full angle)	Temperature control	: TEC
Beam diameter	: <7mm	Operatingtemperature	: -10°C-40°C
Modulation	: >100KHz	Size	: L402xW263xH211mm
Modulation way	: linear analog modulation	Weight	: 21kg
Scanner type	: PT-A30HM	Operating voltage	: 100-240V50/60Hz
Scanning	: 30Kpps@8°	Power consumption	: 600W

Product Views



front



back



right



left

Dimension

